Biological Water Gas Shift

DOE Hydrogen, Fuel Cell, and Infrastructure Technologies Program Review May 19-22, 2003

Pls: Ed Wolfrum and Pin-Ching Maness

Team Members: Andy Watt, Gary Vanzin

Jie Huang and Sharon Smolinski

National Renewable Energy Laboratory



Process Overview

• In the Water-gas Shift (WGS) reaction, CO is oxidized to CO₂ while water is reduced to hydrogen:

$$CO + H_2O \longleftrightarrow CO_2 + H_2$$


- This process is used industrially to produce additional H₂ from synthesis gas streams using a 2-stage catalytic reactor (FeO/Cr at 450°C, CuO/ZnO at 250°C)
- Several strains of photosynthetic bacteria, isolated from the natural environment by NREL researchers, are able to perform the WGS reaction at ambient temperatures
- This may be an attractive alternative to conventional processes
 - Heat Integration Issues
 - Biological vs. Chemical Catalyst
 - Overall System Costs


Relevance/Objective

Objective: to Improve Biological Water-Gas Shift (WGS) for Producing Biomass-Derived H₂.


- Barrier H Cost of Biomass-derived H₂
- Task 4 –Alternatives and Improvements to Conventional WGS
- Two Milestones
 - Verify operation of 100psi WGS Bioreactor (go/no go)
 - Demonstrate 100-L WGS Bioreactor

WGS Flow Chart - Conventional & Biological









Technical Approach

Key Challenges

- Physiology and Molecular Biology:
 - Increase specific water-gas shift rate
 - Eliminate induction period for water-gas shift
- Integrated Engineering and Operation:
 - Increase reactor productivity
 - Operate reactors at elevated pressures

Our Approach to Overcome these Challenges

- Understanding Leads to Solutions
- Physiology and Molecular Biology:
 - Understand the microbe's genetic system for genetic engineering
- Integrated Engineering and Operation:
 - Understand high-pressure bioreactor dynamics

Project Timeline - Biology

Project Steps	FY99	FY00	FY01	FY02	FY03
Improved CO shift rate by more than 5 fold by improving CO mass transfer					
Demonstrated O ₂ tolerance of the hydrogenase; half-life of 21 hours in full air		~			
H ₂ was produced from water in a linked cyanobacterial-hydrogenase hybrid system			×		
Isolated mutants and cloned 2 water-gas shift genes				~~~	
Cloned 8 genes in the watergas shift – manipulate genes to improve H ₂ production					

Accomplishment 1:

Cloned 9 Genes in Water-gas Shift Reaction


CO + H₂O
$$\xrightarrow{coo \text{ F, S, C}}$$
 CO₂ + 2e⁻¹ + 2 H⁺

$$2 \text{ H}^+ + 2\text{e}^{-1} \xrightarrow{coo \text{ M, K, L, X, U, H}} \text{ H}_2$$

- 9 water-gas shift genes are completely sequenced
- WGS-genes complementation was successful, which could lead to over-expression of WGS activity
- With sequences known, these genes can be manipulated to improve H₂ production
- ➤ Meeting FY03 milestone of understanding genetic system of CO shift to allow for manipulations to increase H₂ production

Accomplishment 2:

Water-gas Shift Yields Energy in Darkness



- CO supports both cell growth and ATP synthesis, in darkness
- ATP can be used to regenerate more water-gas shift catalysts in darkness
- Dark bioreactor simplifies reactor design, operation, and reduces cost

Addressing Review Panel's comments that shift reaction can support cell growth yielding energy in darkness leading to sustained H₂ production

Project Timeline - Engineering


Project Steps	FY99	FY00	FY01	FY02	FY03
Test new biological WGS reactor designs					
Evaluate improved reactor internals					
Condition biomass-derived syngas; Demonstrate bioreactor operation at 5-L scale			~		
Operate bioreactor at P=10 atm; Measure shift kinetics of <i>Rx. gelatinosus</i>				—	
Determine Cause of Elevated Pressure Inhibition of WGS Reaction					

This project has a go/no go decision in FY06 to verify 100 psi operating pressure water-gas shift bioreactor at 95% CO conversion efficiency


Accomplishment 3:

Elevated Pressure Bioreactor Operation


- Trickle Bed Reactor (TBR)
 provided good gas-liquid mass
 transfer, but was difficult to
 control and analyze
- Developed a novel
 Recirculating Bubble-Column
 Reactor (RBR) which provides
 good gas-liquid mass transfer,
 and is easier to control and
 analyze



RBR Design Provides Stable Operation at Elevated Pressure



Reactor Pressure (atm)




•Laboratory facilities can accommodate five parallel 1-L bioreactors at pressures up to 20 atm with automated GC analysis of inlet & outlet streams



Accomplishment 4:

Intrinsic Bacterial Kinetics of *Rx. gelatinosus* CBS show Inhibition at Elevated [CO]




Collaborations/Industry Interactions

- Collaborations
 - Washington State University
 - Fundamental studies on the energetics of the watergas shift pathway
 - University of Victoria (Canada)
 - Proteomics-based investigations of the water-gas shift pathway
- Industry Interactions via Work for Others
 - Oil Refinery Service Co.
 - Convert CO in refinery gas to additional hydrogen via biological water-gas shift

Publications

- Maness and Weaver. 2002. "Hydrogen production from a carbon-monoxide oxidation pathway in *Rubrivivax gelatinosus*." *International J. Hydrogen Energy*. 27: 1407-1411.
- Merida, Maness, Brown, and Levin. "Enhanced hydrogen production from indirectly heated biomass, and removal of carbon gas emission using a novel biological gas reformer. Manuscript. Accepted for publication in *International J. Hydrogen Energy*.
- Watt, Huang, Smolinski, Maness and Wolfrum. "The water-gas shift pathway in *Rubrivivax gelatinosus*." Manuscript in preparation.
- Wolfrum, Watt, Amos "Bioreactor Design Studies at Elevated Pressures", Manuscript in Preparation.
- Abstracts submitted for presentation at "12th Western Photosynthesis Conference" and "25th Symposium on Biotechnologies for Fuels and Chemicals."

Comparison of Conventional vs. Biological Water-Gas Shift; Reforming Controls Choice



Results of Techno-Economic Analysis

- The biological water-gas shift reaction (like other biological processes) is slower than the corresponding catalytic process
- The biological reactor will inevitably be larger than the corresponding chemical reactor
- Overall cost savings result from balance-of-plant considerations
- For the biological WGS process, savings result from avoiding steam reformer & associated equipment

Plans and Future Milestones - Biology

- The hydrogenase enzyme system from *Rubrivivax gelatinosus* is unique in its high rate of hydrogen evolution and its tolerance to oxygen, <u>unlike any other hydrogenases</u> reported in literature
- Continued molecular biological study of this organism could lead to other applications:
 - genetic transfer of the hydrogenase into a cyanobacterium (bluegreen alga) to produce hydrogen from water
 - a two-stage "fermentation/photofermentation" process to convert biomass to hydrogen via fermentation and the low-value waste organic acids from which are converted into additional hydrogen in a second-stage photofermentation reaction
 - high-value co-product generation during hydrogen production
- Milestone: increasing WGS activity two-fold through genetic engineering

Plans and Future Milestones - Engineering

- Elevated-pressure bioreactor operation with gaseous substrates is a unique research area
- Continued research in this area could lead to process improvements and other applications:
 - niche applications for low-HC syngas streams
 - elevated pressure reactor stability issues
 - coproduct production (e.g., SCP, PHA)
 - reactor engineering for two-stage"fermentation/photofermentation" process
- Milestone: long-term operation of laboratory-scale elevated pressure bioreactors (>4 months)

Reviewers' Comments - Biology

- Try to understand water-gas shift metabolic pathway and probe the genes
 - 9 genes have been sequenced, which will be used to construct a water-gas shift metabolic pathway and to conduct genetic engineering to increase hydrogen production (accomplishment 1)
- Demonstrate growth and energy generation in darkness
 - We confirmed that CO supports both cell growth and ATP synthesis in darkness, both of which could sustain hydrogen production (accomplishment 2)
 - More robust dark bioreactor would lower cost of hydrogen
- Determine lower limit to which water-gas shift can be driven by the biological system even though commercial operation may not work near this limit
 - water-gas shift rates were determined in various CO concentrations.
 Results indicated that at 3.6% gaseous CO (26 μM dissolved),
 water-gas shift rate is 50% maximum (accomplishment 4)

Reviewers' Comments - Engineering

- *Is pH causing inhibition at elevated pressures?*
 - No; experiments with buffer disprove this; likely substrate or product inhibition
- What will the reactor(s) look like? Low-cost reactors inconsistent with elevated pressure operation
 - Biological reactors will be larger than corresponding high-temperature catalytic reactors; Cost savings may result from less-expensive materials, but balance-ofplant costs will likely control economics